



# SABA Sealcoat CR-T

conductive and high chemical resistant coating for vertical surfaces

## Description

SABA Sealcoat CR-T is a 2-component, thixotropic, crack-sealing, elastic polysulphide-based coating for coating vertical surfaces. Due to its high chemical resistance and conductive character, this product is suitable for a variety of applications in the chemical industry.

## Field of application

Civil & environmental engineering, including the chemical industry. SABA Sealcoat CR-T is especially suitable for coating vertical surfaces made of concrete, stone, tiles and metal, and for coating liner material in calamity rooms, tanks and silos, reservoirs and gutters.

## Advantages

- thixotropic
- durable and weather-resistant
- can be used on concrete structure for emergency storage, prefab constructions, for example
- resistant to solvents and chemicals, resistant to motor fuels such as petrol, diesel oil, hydraulic oil and LPG
- contains no solvents
- conforms to DIBt, Allgemeine bauaufsichtliche Zulassung Z-59.12-201, coating systems for concrete in LAU facilities (only the grey variant)

## Method of use

For more information about the method of use and pre-treatment, see the relevant SABA info sheets and pre-treatment tables at [www.saba.nl](http://www.saba.nl)

## Technical data

	Part A	Part B
<b>Basis</b>	polysulphide	anorganic peroxide
<b>Viscosity</b>	thixotropic	approx. 30 Pa.s
<b>Density</b> (EN 542)	approx. 1,470 kg/m <sup>3</sup>	approx. 1,690 kg/m <sup>3</sup>
<b>Solids content</b>	approx. 100%	approx. 100%
<b>Application time</b>	approx. 1.5 hours	
<b>Curing time</b> (23 °C, 50% RLV)	approx. 20 hours	
<b>Hardness Shore A</b> (EN ISO 868)	approx. 45	
<b>Volume alteration</b> (EN ISO 10563)	approx. 2%	
<b>Working temperature</b>	min. + 5 °C to max. + 35 °C	
<b>Storage temperature</b>	min. + 5 °C to max. + 25 °C	
<b>Temperature resistance</b>	min. - 40 °C to max. + 120 °C	

## Order information

Packaging	set (A and B components)			
<b>Contents</b>	2.5 litre (contains 4 items)	7.5 litre (contains 1 item)	2.5 litre (contains 4 items)	7.5 litre (contains 1 item)
<b>Colour</b>	grey	grey	black	black
<b>Article no.</b>	100286 ABG	100286 ABE	100541 ABG	100541 ABG
<b>Shelf life</b>	18 months (in unopened packaging)			

*Other packaging and colours on request. The shelf life may vary for large packaging.*

## Safety recommendations

For more information about safety, see the relevant SABA safety data sheets.